




14

Declaration of performances  
(Regulation (EU) Nr. 305/2011)

DoP 100

1	Celenio by HARO			EN 13986: 2015
2	Floor covering for internal use under dry conditions			
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim			
4	System of assessment and verification of constancy of performance			3 <sup>*)</sup>
	Thickness	6,5 mm	Silent Pro +2 mm	Silent CT +2 mm
	Density	> 900 kg/m <sup>3</sup>		
	Key properties			
	Bending strength	≥ 13 N/mm <sup>2</sup>		
	Durability, transverse tensile strength	≥ 0,28 N/mm <sup>2</sup>		
	Reaction to fire <sup>*)</sup>	C <sub>FI</sub> - s1 <sup>**)</sup>		
	Emission of formaldehyde <sup>*)</sup>	E1		
	Content of PCP	PCP ≤ 5x10 <sup>-6n</sup>		
	Emission of other dangerous substances	NPD		
	Thermal conductivity	0,154 W/mK	0,072 W/mK	0,050 W/mK
	Natural durability	1 (EN 335-1)		
	Airborne sound insulation, Acoustic absorption, Water vapour permeability, Air permeability	NPD		
6	<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p> <p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> Head of production</p> <p><i>Stephanskirchen, 27.06.2018</i></p> 			
	<p><sup>*)</sup> In accordance with the harmonised standard specified in (1), the inspection body/bodies (NB 2097 eco-Institut, NB 0767 MPA Dresden) has/have performed type testing according to the system specified in (4), and has/have issued a Certificate of Conformity.</p> <p><sup>**)</sup> The outlined fire related characteristics are only valid where the installation has been carried out in accordance with the manufacturer's instructions.</p>			