



13

Declaration of performances  
(regulation (EU) Nr. 305/2011)

DoP 102

1

HARO Corkett

EN 14041

2

Floor covering for internal use under dry conditions

3

Hamberger Flooring GmbH &amp; Co.KG, Postfach 100353, 83003 Rosenheim

4

System of assessment and verification of constancy of performance

3<sup>\*)</sup>

5

Thickness

10,5 mm

11 mm

Key properties

Reaction to fire<sup>\*)</sup>E<sub>FI</sub> - s1

PCP concentration

 $\leq 5 \times 10^{-6n}$ Emission of formaldehyde<sup>\*)</sup>

E1

Water resistance

NPD

Slip resistance

NPD

Electrical behaviour

&lt; 2kV

Thermal conductivity

0,111 W/mK

0,107 W/mK

Durability as regards reaction to fire

NPD

EN 14041:  
2004  
+AC:2005  
+AC:2006

6

The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,  
head of production

Stephanskirchen, 17.02.2016

<sup>\*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).