




13

Declaration of performances  
(regulation (EU) Nr. 305/2011)

DoP 111

1	Multi layer parquet, 2-layer-parquet						EN 13489: 2003
2	Floor covering for internal use under dry conditions						
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim NDS 08-821						
4	System of assessment and verification of constancy of performance					3 <sup>*)</sup>	
	Thickness	7 mm	9 mm	10 mm	10,5 mm (HDF)	12 mm	
	Mass density	>500 kg/m <sup>3</sup>					
	Key properties						
	Reaction to fire <sup>*)</sup>	D <sub>Fl</sub> - s1					
	Emission of formaldehyde <sup>*)</sup>	E1					
	Content of PCP	≤ 5x10 <sup>-6n</sup>					
	Emission of other dangerous substances	NPD					
	Breaking strength	NPD					
	Slip resistance	NPD					
	Thermal conductivity	0,200 W/mK	0,186 W/mK	0,132 W/mK	0,184 W/mK	0,133 W/mK	
	Natural durability	1 (DIN EN 350-1:1994)					
6	<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p> <p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> <i>head of production</i></p> <p><i>Stephanskirchen, 22.03.2017</i></p> 						
	<p><sup>*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0765 WKI Braunschweig, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).</p>						

EN 14342:  
2003