




13

Declaration of performances  
(regulationn (EU) Nr. 305/2011)

DoP 118

1	Hamberger multi layer parquet Carré	EN 13489: 2003
2	Floor covering for internal use under dry conditions	
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim	
4	System of assessment and verification of constancy of performance	3 <sup>*)</sup>
	Thickness	16 mm
	Mass density	>500 kg/m <sup>3</sup>
	Key properties	
	Reaction to fire <sup>*)</sup>	D <sub>Fl</sub> - s1
	Emission of formaldehyde <sup>*)</sup>	E1
	Content of PCP	≤ 5x10 <sup>-6n</sup>
	Emission of ather dangerous substances	NPD
	Breaking strength	NPD
	Slip resistance	NPD
	Thermal conductivity	0,133 W/mK
	Natural durability	1 (DIN EN 350-1:1994)
6	<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p> <p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> <i>head of production</i></p> <p><i>Stephanskirchen, 17.02.2016</i></p> 	
	<p><sup>*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0765 WKI Braunschweig, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).</p>	

EN 14342:  
2003