

Declaration of performances (regulation (EU) Nr. 305/2011)

## **DoP 147**

1	Hamberger Multi layer parquet 10mm Permadur DIN EN 13489:20		13489:2017		
2	Floor covering for internal use under dry conditions				
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83071 Stephanskirchen				
4	System of assessment and veri	assessment and verification of constancy of performance			
5	Thickness	10mm			
	Mass density	> 500 kg/m³			
	Key properties				
	Reaction to fire*)	C <sub>FI</sub> - s1		EN 14342: 2013	
	Emission of formaldehyde <sup>†)</sup>	E1			
	Content of PCP	≤ 5x10 <sup>-6n</sup>			
	Emission of other dangerous substances	NPD			
	Breaking strength	NPD			
	Slip resistance	NPD			
	Thermal conductivity	0,132 W/mK			
	Natural durability	1 (DIN EN 350-1:1994)			

The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber, head of production

Stephanskirchen, 03.05.19

In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0765 WKI Braunschweig, NB 0766 eph Dresden, NB 1378 Exova Brandhaus) has/have performed type testing according to the system specified in (4).