




16

Declaration of performances  
(regulation (EU) Nr. 305/2011)

DoP 149

1	Hamberger Designboden				EN 14041
2	Floor covering for internal use under dry conditions				
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim				
4	System of assessment and verification of constancy of performance				3 <sup>*)</sup>
5	Thickness	2 mm	6,5 mm	8 mm	9,3 mm
	Key properties				
	Reaction to fire <sup>*)</sup>	C <sub>FI</sub> - s1	D <sub>FI</sub> - s1		
	PCP concentration	$\leq 5 \times 10^{-6n}$			
	Emission of formaldehyde <sup>*)</sup>	E1			
	Water resistance	NPD			
	Slip resistance	DS			
	Electrical behaviour	< 2kV			
	Thermal conductivity	0,147 W/mK	0,141 W/mK	0,17 W/mK	0,144 W/mK
Durability as regards reaction to fire	NPD				
6	<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p> <p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> <i>head of production</i></p> <p><i>Stephanskirchen, 16.02.2017</i></p> 				
<sup>*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).					