



16

Declaration of performances
(Regulation (EU) Nr. 305/2011)

DoP 151

1

HARO Interior Wall

EN 14915 :
2013

2

Siding for internal use under dry conditions

3

Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim

4

System of assessment and verification of constancy of performance

3^{*)}

Thickness

4,5mm

5,5mm

8,1mm

Key properties

Reaction to fire^{*)}

E

Emission of formaldehyde^{*)}

E1

PCP concentration

 $PCP \leq 5 \times 10^{-6n}$ Emission of other dangerous substances^{*)}

NPD

Acoustic absorption

NPD

Thermal conductivity

Design wood: 0,155 W/mK
ComforTec: 0,050 W/mK

Fixing resistance

NPD

Natural durability

1
(DIN EN 350-1:1994)EN 14915 :
2013

6

The performance of the product identified in (1) is in conformity with the declared performance in (5).
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,
Head of production

Stephanskirchen, 11.01.2017

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut) has/have performed type testing according to the system specified in (4).