

## Technical information

### aqua oil

Art. no. 407 718



---

Product	Initial treatment and subsequent maintenance of pre-oiled surfaces (cork flooring and parquet)	
Instructions	The floor must be cleaned thoroughly (dust-free) before applying Aqua Oil. The surface must be free of dust and other contaminants. For cleaning we recommend the use of clean & green active, diluted and applied as per instructions. Before applying aqua oil, shake the container well and pour undiluted into a suitable bucket/container. Absorb aqua oil into a mop/applicator and apply evenly in thick coats, and in overlapping straight lines. Always apply lengthways, along the direction of the board. The floor is accessible again after about 2 hours and can be cleaned after 2 days.	
Ingredients	Desiccants free of heavy metals, < 5% non-ionic tensides, wax and vegetable oil components and water. Meets the requirements of DIN EN 71 -3 (free of heavy metals).	
Technical data	pH value:	approx. 8.0
	Giscode:	Ö10/GH0
	Coverage	1,000 ml cover approx. 50 m <sup>2</sup> 20 - 25 ml/m <sup>2</sup>
	Shelf life:	3 years
	Colour:	Milky, beige
	Form:	Liquid

#### Note:

DE/032/031



- Keep out of reach of children
- Clean work materials with water immediately after use.
- Protect from frost!
- Use opened containers quickly.
- Close containers immediately after use.
- Dispose of dried product residue via residual waste.
- Dispose of liquid product residue via local collection points.

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.